



Main

| | |
|---------------------------|--------------------------|
| Range of product | Easy Modicon M200 |
| Product or component type | Analogue input cartridge |
| Product compatibility | Easy Modicon M200 |
| Analogue input number | 2 |

Complementary

| | |
|--|---|
| Analogue input type | Current 4...20 mA Current 0...20 mA Voltage 0...10 V |
| Analogue input resolution | 12 bits |
| LSB value | 2.44 mV 0...10 Vvoltage 4.88 μ A 0...20 mAcurrent 3.91 μ A 4...20 mAcurrent |
| Conversion time | 20 ms |
| Sampling duration | 10 ms |
| Absolute accuracy error | +/- 0.1 % of full scale at 25 °C +/- 1 % of full scale |
| Temperature drift | +/- 0.02 %FS/°C |
| Repeat accuracy | +/- 0.5 %FS |
| Non-linearity | +/- 0.01 %FS |
| Cross talk | <= 1 LSB |
| Type of cable | Twisted shielded pairs cable |
| Electrical connection | 3 x 1.5 mm ² 2 screw terminal blocks with pitch 3.81 mm adjustment for inputs |
| Maximum cable distance between devices | Twisted shielded pairs cable: <30 m for input |
| Insulation | Non-insulated between analogue input and internal logic |
| Height | 41 mm |
| Depth | 15 mm |
| Width | 35 mm |
| Net weight | 0.012 kg |
| Permissible continuous overload | 13 V, analogue input type: voltage 40 mA, analogue input type: current |
| Input impedance | <= 250 Ohm current >= 1 MOhm voltage |

Environment

| | |
|-------------------------|-------|
| Immunity to microbreaks | 10 ms |
|-------------------------|-------|

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.589 cm |
| Package 1 Width | 4.772 cm |
| Package 1 Length | 7.056 cm |
| Package 1 Weight | 30 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 75 |
| Package 2 Height | 15 cm |
| Package 2 Width | 30 cm |
| Package 2 Length | 40 cm |
| Package 2 Weight | 2.815 kg |
| Unit Type of Package 3 | P12 |
| Number of Units in Package 3 | 2400 |
| Package 3 Height | 100 cm |
| Package 3 Width | 125 cm |
| Package 3 Length | 55 cm |
| Package 3 Weight | 85 kg |

Offer Sustainability

| | |
|----------------------------|---|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |