

ZCE28

Limit switch head, Limit switches XC Standard, ZCE, roller lever plunger horizontal or vertical direction



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



Main

| | |
|---------------------------|--|
| Range of product | Telemecanique Limit switches XC Standard |
| Series name | Standard format |
| Product or component type | Limit switch head |
| Device short name | ZCE |
| Head type | Plunger head |
| Product compatibility | XCMD XCKT XCKP XCKD |

| | |
|----------------------------|--|
| Associated body | ZCMD21C12 ZCMD21L08U78 ZCMD25L5 ZCT21G11 ZCMD41L1 ZCT27P16 ZCD29M12 ZCD21 ZCP37 ZCMD41L2 ZCD25 ZCMD21L5 ZCMD39L1 ZCP27 ZCP35 ZCP28 ZCT28G11 ZCT26N12 ZCD39 ZCT25G11 ZCMD39L5 ZCT21P16 ZCP25 ZCMD81L1 ZCD31 ZCT28P16 ZCMD81L5 ZCMD69C12 ZCT27N12 ZCD21M12 ZCT25N12 ZCD26 ZCP21M12 ZCP39 ZCMD25L1 ZCT25P16 ZCT21N12 ZCP29 ZCMD37L2 ZCMD61C12 ZCD28 ZCD37 ZCT26G11 ZCP21 ZCMD81L2 ZCMD37L1 ZCMD25L2 ZCP29M12 ZCMD29L1 ZCMD37L5 ZCMD41L5 ZCMD21M12 ZCT28N12 ZCT26P16 ZCMD21L08R12 ZCMD21L1 ZCP26 ZCD27 ZCMD29L2 ZCT27G11 ZCMD39L2 ZCMD61M12 ZCP31 ZCD35 ZCMD21L2 ZCMD29C12 ZCMD29L5 ZCD29 |
| Movement of operating head | Linear |
| Type of operator | Roller lever plunger spring return thermoplastic |
| Type of approach | Lateral or vertical approach, 1 direction |

Complementary

| | |
|------------------|------------|
| Switch actuation | By 30° cam |
| Positive opening | With |

Environment

| | |
|---------------------------------------|----------------------|
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Environmental characteristic | Standard environment |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.6 cm |
| Package 1 Width | 5.0 cm |
| Package 1 Length | 3.0 cm |
| Package 1 Weight | 26.0 g |
| Unit Type of Package 2 | BAG |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 3 cm |
| Package 2 Width | 13 cm |
| Package 2 Length | 28 cm |
| Package 2 Weight | 265 g |
| Unit Type of Package 3 | S01 |
| Number of Units in Package 3 | 80 |
| Package 3 Height | 15 cm |
| Package 3 Width | 15 cm |
| Package 3 Length | 40 cm |
| Package 3 Weight | 2.46 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|